

MATERIAL SAFETY DATA SHEET

8/18/98

SECTION 1- MATERIAL AND MANUFACTURER IDENTIFICATION

PRODUCT NAME: DRITAC REPAIR ADHESIVE (DT-4677-3M)

HMIS CODES: H-1, F-0, R-0, P-A

MANUFACTURER'S NAME: DRITAC ADHESIVE GROUP EMERGENCY PHONE:1-800-535-5053

ADDRESS: 59 INGRAHAM ST. BROOKLYN, NY 11237 INFORMATION PHONE:1-718-497-5200

SECTION 2-HAZARDOUS INGREDIENTS /SARA III INFORMATION

HAZARDOUS COMPONENTS: CAS NUMBER OSHA PEL ASCII TLV VAPOR PRESSURE WEIGHT PERCENT

NO CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 TITLE III AND OF 40 CFR 372 ARE PRESENT

SECTION 3-PHYSICAL/CHEMICAL CHARACTERISTICS

SPECIFIC GRAVITY (H20=1) 1.0 ; COATING VOC: 0

SOLUBILITY IN WATER: DISPERSIBLE

APPEARANCE AND ODOR: WHITE MILKY LIQUID; MILD AMMONIA ODOR

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA: FLASH POINT; NONE FLAMMABLE LIMITS IN AIR BY VOLUME: LOWER N/A UPPER N/A

EXTINGUISHING MEDIA: FOAM,CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES: WHEN DRIED MATERIAL BURNS, WATER, CARBON DIOXIDE, CARBON MONOXIDE, AND SMOKE ARE PRODUCED. PYROLYSIS PRODUCTS MAY INCLUDE SOME HAZARDOUS MATERIALS. USE RECOMMENDED BREATHING APPARATUS FOR PROTECTION FROM SUCH HAZARDS.

SECTION 5 - REACTIVITY DATA

STABILITY: STABLE CONDITIONS TO AVOID: AVOID CONTACT WITH STRONG OXIDIZING AGENTS AND ANY WATER SENSITIVE MATERIAL HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON DIOXIDE AND CARBON MONOXIDE.

SECTION 6 -HEALTH HAZARD DATA

EFFECTS OF OVER EXPOSURE: VAPORS MAY CAUSE RESPIRATORY IRRITATION, NAUSEA, HEADACHE.

PROLONGED SKIN AND ANY EYE CONTACT MAY CAUSE IRRITATION AND REDDENING. INGESTION MAY CAUSE VOMITING, NAUSEA, DIARRHEA. MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: CURRENT ANEMIA, RESPIRATORY OR LIVER AILMENTS, AND PREEXISTING SKIN CONDITIONS.

EMERGENCY AND FIRST AID PROCEDURES:

IF SPLASHED IN THE EYE, FLUSH WITH A LOT OF WATER FOR 15 MINUTES AND SEEK MEDICAL HELP IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR AND APPLY ARTIFICIAL RESPIRATION IF NEEDED. CALL A PHYSICIAN. INGESTION: DRINK 1 OR 2 GLASSES OF WATER AND CONSULT A PHYSICIAN. WASH SKIN WITH SOAP AND WATER.

SECTION 7-PRECAUTIONS FOR SAFE HANDLING AND USE

SPILLS: PUT WASTE MATERIAL INTO A DOT APPROVED CONTAINER. DO NOT FLUSH ADHESIVE DOWN A DRAIN AS IT CAN PLUG THE DRAIN PIPES. DISPOSE OF WASTE ONLY IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. VENTILATION: USE IN A WELL VENTILATED AREA. A SLIGHT AMMONIA ODOR MAY BE PRESENT UNTIL THE ADHESIVE DRIES. PROTECTIVE EQUIPMENT: USE GLOVES AND SAFETY GLASSES TO PROTECT EYES. AVOID EXTREME HEAT AND PREVENT FROM FREEZING.

KEEP OUT OF REACH OF CHILDREN

SECTION 8-DISCLAIMER

THE INFORMATION IN THIS MSDS HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, WE PROVIDE NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, AND WE ASSUME NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN. UNDER VARIOUS CONDITIONS THE INGREDIENTS MAY POSE A LESSOR OR GREATER HAZARD TO DIFFERENT INDIVIDUALS. IT IS THE USER'S RESPONSIBILITY TO SEE THAT THE DATA IS COMPLETE FOR THEIR USE.