

MATERIAL SAFETY DATA SHEET

DriTac Adhesive Group – 59 Ingraham Street, Brooklyn, NY 11237
(718) 497-5200 - FAX (718) 366-1425

SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME: DriTacWipe-Aways Urethane Adhesive Remover

CHEMICAL: Not Applicable, mixture SYNONYMS: None

EMERGENCY MEDICAL AND SPILL NUMBER 1-866-359-5661

SECTION 2 COMPONENT & EXPOSURE DATA

COMPONENT	CAS#	PEL	TLV	%
DIMETHYL GLUTERATE	1119-40-0	28-35		
DIMETHYL ADIPATE	627-93-0	9-18		

SECTION 3 HEALTH INFORMATION

EFFECTS OF OVEREXPOSURE: May cause eye and respiratory tract irritation-May cause blurred vision
EYE CONTACT: This material may cause pain,redness, and tearing based on toxicity studies. May cause blurred vision.
SKIN CONTACT: This material may cause skin irritation. Prolonged or repeated exposure may cause redness, burning, drying or cracking of skin or dermatitis.
INHALATION: This product may cause coughing, chest tightness, chest pain, and runny nose based on toxicity studies.
INGESTION (SWALLOWING): LD50>50ml/kg (albino rats)(similar products)

SECTION 4 OCCUPATIONAL EXPOSURE LIMITS

PEL: NO OSHA PEL TLV: NO ACGIH TLV

SECTION 5 EMERGENCY FIRST AID PROCEDURES

FOLLOW STANDARD FIRST AID PROCEDURES:
SWALLOWING: Call physician or poison control center.
SKIN CONTACT: Wash affected area.
EYE CONTACT: Flush eyes with cool water for at least 15 minutes. Do not let victim rub eyes.
INHALATION: Immediately remove victim to fresh air. Get medical attention immediately.

SECTION 6 PHYSICAL DATA

BOILING POINT: Over 400 degrees F (204 degrees C) at 760 mm Hg pressure
MELTING POINT: -1 degree C
VAPOR PRESSURE: Less than .1 mm Hg at 72 degrees F
SPECIFIC GRAVITY: 0.97 AT 25 degrees c
SOLUBILITY IN WATER: Negligible at room temperature
APPEARANCE AND COLOR: Light yellow to clear and liquid at room temperature
ODOR: Light musty odor

SECTION 7 FIRE AND EXPLOSION HAZARDS

FLASH POINT & METHOD USED: < 141 degrees fahrenheit (PMCC)
FLAMMABLE LIMITS: Not applicable NFPA RATING: No NFPA rating

HMIS RATING: HEALTH: 1 FIRE: 1 REACTIVITY: 0

SPECIAL FIRE FIGHTING PROCEDURES & PRECAUTIONS: Treat as oil fire. Use water spray, dry chemical, foam or carbon dioxide.
USUAL FIRE & EXPLOSION HAZARDS: Rags soaked with any solvent present a fire hazard and should always be stores in UL listed of Factory Mutual approved, covered containers. Improperly stored rags can create conditions that lead to oxidation. Oxidation, under certain conditions can lead to spontaneous combustion. This product contains antioxidants to retard oxidation.

SECTION 8 REACTIVITY

STABILITY: Stable HAZARDOUS POLYMERIZATION: None Likely
MATERIAL TO AVOID: Strong oxidizing agents HAZARDOUS DECOMPOSITION PRODUCTS: CO2, CO
CONDITIONS TO AVOID: Strong oxidants, acids and alkalis

SECTION 9 EMPLOYEE PROTECTION

CONTROL MEASURES; Adequate Ventilation
RESPIRATORY PROTECTION: Avoid breathing vapor or mist. Use NIOSH/MSHA approved respiratory protection equipment.
PROTECTIVE CLOTHING: No need anticipated EYE PROTECTION: Wear chemical goggles and have eye flushing equipment available.

SECTION 10 ENVIRONMENTAL PROTECTION

ENVIRONMENTAL PRECAUTIONS: Avoid uncontrolled releases of this material to environment.
SPILL OR LEAK PRECAUTIONS: Contain spilled material. Transfer to secure containers. Where necessary, collect using absorbent media.
WASTE DISPOSAL: Dispose of according to federal, state and/or local requirements.

SECTION 11 REGULATORY CONTROLS

DOT CLASSIFICATION: CLASS 55 DOT PROPER SHIPPING NAME: Cleaning Compound
OTHER REGULATORY REQUIREMENTS: Listed in TSCA inventory

SECTION 12 DOCUMENTARY INFORMATION

DISCLAIMER OF EXPRESSED OR IMPLIED WARRANTIES The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his/her own determination as to the suitability of the product for his/her particular purpose and on the condition the he/she assume the risk of his use thereof.