

BS-5043; UR-1

Page: 1
11/2/2007



PRODUCT NAME: BS-5043; UR-1
PRODUCT CODE: .5543

Page 1

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: Dritac Flooring Products LLC
ADDRESS : 60 Webro Road
Clifton, NJ 07012

EMERGENCY PHONE : 1-800-424-9300 DATE PRINTED : 10/21/2010
INFORMATION PHONE : 1-973-614-9000 NAME OF PREPARER : R&D LAB

=====**SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS**=====

CONTAINS: 35 – 45% 2-BUTOXYETHANOL (111-76-2) [203-905-0],
25 – 30% ETHYL-3-ETHOXYPROPIONATE (763-69-9),
20 – 30% D-LIMONENE (5989-27-5)

=====**SECTION 3. HAZARDS IDENTIFICATION**=====

RISK STATEMENTS:
R10 Flammable.
R22 Harmful if swallowed.
R36/37/38 Irritating to eyes, respiratory system and skin
SAFETY STATEMENTS:
S24/25 Avoid contact with skin and eyes.

=====**SECTION 4. FIRST AID MEASURES**=====

RISK STATEMENTS:
EYE CONTACT:
For eyes, flush with plenty of water for 15 minutes and get medical attention.
SKIN CONTACT:
In case of contact with skin, immediately remove contaminated clothing. Wash thoroughly with soap and water. Wash contaminated clothing before reuse.
INHALATION:
After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. CALL A PHYSICIAN immediately!
SWALLOWING:
If swallowed, CALL A PHYSICIAN IMMEDIATELY! DO NOT induce vomiting. Have patient lie down and keep warm. Vomiting may lead to pneumonitis, which may be fatal.

=====**SECTION 5. FIRE FIGHTING MEASURES**=====

EXTINGUISHING MEDIA
NFPA Class B extinguishers (Carbon Dioxide or foam) for Class II liquid fires.
SPECIAL FIRE FIGHTING PROCEDURES
Water spray may be ineffective on fire but can protect fire-fighters in cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear (Helmet with face shield, bunker coats, gloves and rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.
UNUSUAL EXPLOSION AND FIRE PROCEDURES
COMBUSTIBLE!
Keep container tightly closed. Isolate from oxidizers, heat and open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

M A T E R I A L S A F E T Y D A T A S H E E T

BS-5043; UR-1

Page: 1
11/2/2007

=====SECTION 6. ACCIDENTAL RELEASE MEASURES =====

CONTAINMENT TECHNIQUES

Stop spill at source. Dike area and contain.