

# 8801 OMNISHIELD

Hard Surface Protective Foam



[dritac.com](http://dritac.com)  
[info@dritac.com](mailto:info@dritac.com)

## TECHNICAL DATA SHEET

DriTac 8801 OmniShield provides scratch and dent protection for newly installed floors and surfaces to prevent damage from occurring during and after the installation process. 8801 is porous and will allow sub-surface moisture to pass through. 8801 resists surface spills and water spots on the top of the film surface.

### FOR USE ON

- Concrete
- Wood
- Tile
- Stone
- Linoleum
- LVT
- Carpet and Carpet Tile
- WPC
- Most Floor Types New or Existing
- Countertops
- Furniture
- Cabinets

### ATTRIBUTES

- 1.85 mm thickness
- 4' x 200' = 800 sq. ft./roll
- Anti-Crush Mechanical Properties
- **Water & Stain Resistant:** 8801 protects from stains, oils and chemicals.
- **Tear Resistant:** 8801 has a fused film layer that is puncture resistant.
- **Aerated:** 8801 is scored and features a breathable surface to allow free air flow of surface moisture, while preventing topical water and spills from seeping through.
- **Lays Flat:** 8801 is a grooved foam which remains flush to the floor and helps prevent the risk of tripping or falling on the floor.



**BUILDING TRUST**



# TECHNICAL DATA SHEET

## INSTALLATION INSTRUCTIONS - 4 EASY STEPS

1. Sweep, vacuum, and remove debris from the surface, prior to rolling out 8801.
2. Roll out 8801 over the surface. Always install with the smooth side on top and ridges down.
3. Use non-residue duct tape to secure the flooring sheets together.
4. Connect the rolls together evenly to prevent overlapping from occurring and to avoid gapping between the foam.

### Bonus Step

5. 8801 is reusable, roll it up and transport it to the next job.

## PRECAUTIONS

Installation of this product on staircases may cause slipping or falls when installed. DriTac 8801 OmniShield must be fastened to the skirt boards when used on staircases. Use DriTac 8801 OmniShield at your own discretion.

Use a premium-grade non residue tape, such as 3M's duct tape to bind the seams of 8801 and provide a temporary application over approved surfaces. Always refer to manufacturer specifications and limitations.

## WARRANTY

This product is warranted to be free of manufacturing defects. If a manufacturing defect is found within one year from the date of purchase, such defective product shall be replaced. No warranty either expressed or implied is made regarding the performance of this product since conditions under which these goods are transported, stored, used or applied are beyond our control. This warranty is made in lieu of all other warranties either expressed or implied and the seller shall not be responsible for consequential, incidental, special or other damages no matter what the cause.

## PACKAGING

Available in 800 sf individual product rolls

Rolls/Truckload	260
SF/Truckload	208,000

## TECHNICAL RAPID RESPONSE

(201) 933-8800 Mon-Fri 8am - 5pm EST